



Way of Life!

VITARA

Major Specifications and Equipment



Suzuki's "Way of Life!" is the heart of our brand - every Suzuki vehicle, motorcycle and outboard motor is built to create excitement so customers can enjoy everyday life.



Standard and optional equipment available may vary for individual markets. Please enquire at your dealers, as specifications and illustrations may refer to models not available in your region. SUZUKI MOTOR CORPORATION reserves the right to change, without notice, prices, colours, materials, equipment, specifications and models, and also to discontinue models.

All photographs in this brochure were taken with relevant permission. Images of the vehicles without number plates on public roads are composite photos.

SUZUKI MOTOR CORPORATION
300 Takatsuka-cho, Minami-ku, Hamamatsu-shi, Shizuoka 432-8611 JAPAN
www.globalsuzuki.com

VITARA SPEC AND EQUIPMENT SHEET (G)
99999-BB002-001



DUALTONE



Solar Yellow Pearl Metallic /
Cosmic Black Pearl Metallic (DBH)



Atlantis Turquoise Pearl Metallic /
Superior White (AGH)



Ice Grayish Blue Metallic /
Cosmic Black Pearl Metallic (DBF)



Solar Yellow Pearl Metallic /
Superior White (DBG)



Galactic Gray Metallic /
Cosmic Black Pearl Metallic (A9G)



Savanna Ivory Metallic /
Cosmic Black Pearl Metallic (A9N)



Atlantis Turquoise Pearl Metallic /
Cosmic Black Pearl Metallic (A9L)



Bright Red 5 /
Cosmic Black Pearl Metallic (A9H)

METALLIC



Atlantis Turquoise Pearl Metallic (ZQN)



Cool White Pearl (ZNL)



Silky Silver Metallic 2 (ZCC)



Galactic Gray Metallic (ZCD)



Cosmic Black Pearl Metallic (ZCE)

SOLID



Superior White (26U)



Bright Red 5 (ZCF)

GL



GL+



GLX



Major Specification

Steering	LHD/RHD			
Number of doors	5			
Engine	Petrol			
Drive system	2WD	ALLGRIP	2WD	ALLGRIP

DIMENSIONS		1.6L VVT		1.4L BOOSTERJET	
Overall length	mm	4,175		4,175	
Overall width	mm	1,775		1,775	
Overall height	mm	1,610		1,610	
Wheelbase	mm	2,500		2,500	
Tread	mm	Front	1,535	Front	1,535
	mm	Rear	1,505	Rear	1,505
Minimum turning radius	m	5.2		5.2	
Minimum ground clearance	mm	185		185	

CAPACITY		1.6L VVT		1.4L BOOSTERJET	
Seating capacity	persons	5		5	
	litres	1,120		1,120	
Luggage capacity	litres	Max. volume	710	Rear seatback folded (VDA method)*	375
	litres	Rear seatback raised (VDA method)*	47		
Fuel tank capacity	litres	47		47	

ENGINE		M16A		K14C-DITC	
Type		4		4	
Number of cylinders		16		16	
Number of valves		1,586		1,373	
Piston displacement	cm ³	78.0*83.0		73.0*82.0	
Bore*stroke	mm	11.0		9.9	
Compression ratio		86/6,000		103/5,500	
Maximum output	kW/rpm	153/4,400		220/1,500-4,000	
Maximum torque	Nm/rpm	Multipoint injection		Direct injection	
Fuel distribution					

TRANSMISSION		5MT		6AT		6MT		6AT	
Type		3,545	4,666	3,545	4,666	3,615	4,044	3,615	4,044
	1st	1,904	2,533	1,904	2,533	1,954	2,370	1,954	2,370
	2nd	1,258	1,555	1,258	1,555	1,275	1,555	1,275	1,555
	3rd	0.911	1,135	0.911	1,135	0.942	1,159	0.942	1,159
	4th	0.725	0,859	0,725	0,859	0,794	0,851	0,794	0,851
	5th	-	0,685	-	0,685	0,674	0,672	0,674	0,672
	6th	3,250	3,393	3,250	3,393	3,481	3,193	3,481	3,193
	Reverse	4,411	3,683	4,411	3,683	4,312	3,501	4,312	3,501
Final gear ratio									

CHASSIS		Rack & pinion	
Steering		Ventilated disc	
Brakes	Front	Disc	
	Rear	MacPherson strut with coil spring	
Suspensions	Front	Torsion beam with coil spring	
	Rear	215/60R16, 215/55R17	
Tires			

WEIGHTS		1.6L VVT		1.4L BOOSTERJET	
Kerb weight	kg	1,075-1,165	1,120-1,180	1,160-1,235	1,235-1,260
Gross vehicle weight	kg	1,730		1,730	

PERFORMANCE		1.6L VVT		1.4L BOOSTERJET	
Maximum speed	km/h	180	180	180	200
0-100 km/h	secs	11.5	12.5	12.0	9.5

*Measured without rear parcel shelf.
 All figures are manufacturer's data and may vary for each market.
 For information about official certification data, please contact the SMC marketing group in charge of your area.



